# DMN702G

**MCP Green, emergency door release, double pole free contact, surface mount with glass**

## General

The DMN702G is a green manual call point for surface mount applications. It offers double pole, changeover contacts with common, normally open and normally closed connections. It is supplied with a EN54 breakable glass and test key.

## Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique ‘plug and play’ concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

## Options and approvals

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest ‘flex-ability’, the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



## Details

- Specifically for door security and evacuation
- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatibale
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch

# DMN702G

## MCP Green, emergency door release, double pole free contact, surface mount with glass

## Technical specifications

### General

| | |
|---|---|
| Status indication | Alarm Flag |
| Compatibility | Conventional detection systems |

### Electrical

| | |
|---|---|
| Cable specification | 0.5 to 2.5 mm² (termination) |
| No. of cable cores | 2 |

### Detection

| | |
|---|---|
| Detection principle | Manual activation |
| Installation height | Determined by local regulation |

### Output

| | |
|---|---|
| Output type and rating | 2A @ 30 VDC (resistive load) |

### Physical

| | |
|---|---|
| Net weight | 110 g |
| Colour | Grøn |
| Mounting type | Bagkasse |
| Material (body) | PC / ABS |
| Functional marking | Running man |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Operating temperature | -10 to +55°C |
| Storage temperature | -10 to +55°C |
| Relative humidity | 0 to 95% noncondensing |
| Environment | Indendør |
| IP rating | IP24D |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 2, WEEE |
| Certification | CE |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Detection device | DM715 | EN54 Universal MCP glass, without branding |
| Detection device | DM788GR | Surface Mount Box Without Connectors, Green |
| Detection device | DMN782 | Hinged transparent MCP protection cover |

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 June 2025 - 15:18