# EV669

**PIR plaf. Mont. Met "4-D" sign. Verw. Voldoet aan EN norm grade 2.**



# EV669

## PIR plaf. Mont. Met "4-D" sign. Verw. Voldoet aan EN norm grade 2.

## Technische specificaties

### General

| | |
|---|---|
| Technology | PIR |
| Application type | Ceiling mount |
| Anti masking | No |
| Pet immune | No |
| Camera | No |
| Signal processing | 4D |
| Pry-off tamper kit | ST400 (optional) |

### Detection

| | |
|---|---|
| Max. detection range | 20 m |
| Undercrawl protection | No |
| Alarm memory | Yes |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Wired |

### Inputs/outputs

| | |
|---|---|
| Remote control lines | Day/Night, Walk test |

### Electrical

| | |
|---|---|
| Power supply type | 12 VDC |

### Physical

| | |
|---|---|
| Colour | White |
| Mounting height | 2.5 to 5 m |

### Environmental

| | |
|---|---|
| Environment | Indoor |

### Regulatory

| | |
|---|---|
| EN50131 grade | Grade 2 |
| Certification | NFA2P, VdS |



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57