# ACL800-BC-USB-B

**ACL800 Biometric Capacitive learn-in reader - Fingerprint, Desktop, USB, EM/CASI Prox/HID Prox/ MIFARE Compatible**



# ACL800-BC-USB-B

## ACL800 Biometric Capacitive learn-in reader - Fingerprint, Desktop, USB, EM/CASI Prox/HID Prox/ MIFARE Compatible

## Technische Spezifikationen

### System

| | |
|---|---|
| RTE (Request To Exit) | No |
| CSN (Card Serial Number) | Yes |
| Custom data model | No |

### Technology

| | |
|---|---|
| Reader type | BioMetric, Proximity, Smart Card |
| Reader operating-transmitting frequency | 125 KHz, 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE UltraLight (CSN) |
| Supported technology 125 kHz | EM4102, GE ProxLite/CASI Prox, HID Prox |
| Mifare type | ISO14443A |
| No. of Mifare bytes CSN | 4 Bytes (S50), 7 Bytes (S70) |
| Read write | No |
| SAM module embedded | No |

### Biometric

| | |
|---|---|
| Biometric type | Fingerprint |
| Biometric sensor type | Capacitive |

### Interface & connections

| | |
|---|---|
| Interface | Wiegand |
| Connector type | Pigtail |

### Tamper type

| | |
|---|---|
| Pry-off tamper | No |
| Opening tamper | Yes |

### Operation

| | |
|---|---|
| Stand-alone | No |
| PIN keypad | No |

### Electrical

| | |
|---|---|
| Power supply type | USB |

### Physical

| | |
|---|---|
| Colour | Black |
| Material | ABS |
| Form factor | Oversized |
| Mounting type | Surface mount |

### Environmental

| | |
|---|---|
| Environment | Indoor, Outdoor |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS |

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.