AS507

Outdoor siren with single blue beacon



Details

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Self detection of cable cutting or tampering
- Installer Friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

AS507

Outdoor siren with single blue beacon

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	114 dB at 1 m (typical)
Comfort LED	Yes

Flash specifications

Flash frequency	50 to 60 flashes/min

Electrical

Operating voltage	10 to 14.5 VDC
Current consumption	350 mA 40 mA (standby, with NiCd battery) 20 mA (standby, without battery)

Physical

Physical dimensions	210 x 300 x 55 mm (W x H x D)
Net weight	1023 g
Material	Polycarbonate
Material	Polycarbonate (3 mm)
Metal inner cover	Optional

Environmental

Operating temperature	-25 to 55°C
IP rating	IP54

Sounder

Type	Double piezo
Cut-off timer	3, 5, 10, 20 min
Frequency	0.5 to 3 kHz

Security

Low voltage detection	Yes
Tamper & pry-off	Yes
PCB protection	Fully potted

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 27 May 2026 - 17:12