# 9-10945

## Standard sampling point assembly - complete with detacable sampling point

### Description

The 9-10945 is a flush mount, capillary sampling point for use with false ceilings. It is supplied complete with a 27mm diameter t-union, to which the flexible sample pipe connects. The flexible sampling pipe has a diameter of 10mm and is 1m long. At the end of the flexible sampling pipe, the sampling point is connected which fits onto the false ceiling.



### Details

- Flush mount sampling point

# 9-10945

## Standard sampling point assembly - complete with detacable sampling point

## Technical specifications

### Physical

| | |
|---|---|
| Physical dimensions | 36 mm (Sampling point diameter)<br>10 mm (Outer capalliry pipe diameter)<br>1 m (length)<br>27 mm (Inner T-Union diameter) |
| Colour | White |
| Mounting type | Insert |

### Environmental

| | |
|---|---|
| Environment | Indoor |

### Regulatory

| | |
|---|---|
| Certification | EN54-20 |

### Samlping point

| | |
|---|---|
| diameter | 36 mm |
| color | White |

### Sampling pipe

| | |
|---|---|
| diameter | 10 mm (outer) |
| length | 1 m |
| color | Red |

### T-union

| | |
|---|---|
| diameter | 27 mm (inner) |
| color | Red |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 December 2024 - 9:26