VE1016

Vector PIR, DSP, 16 m, 9 curtains



Details

- Passive Infra Red motion sensor
- 3-Step Gliding Focus Curtain mirror
- Plug-in electronics
- Sealed optics
- "V2E" signal processing for false alarm immunity
- Cloak and umbrella immunity
- Full under crawl detection
- Selectable coverage pattern using mirror masks
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- EN50131-2-2 Grade 2 certified
- Several European approvals

VE1016
Vector PIR, DSP, 16 m, 9 curtains

Technische specificaties

General

Technology	PIR
Application type	Wall mount
Anti masking	No
Pet immune	No
Camera	No
Signal processing	Vector Verified Enhanced (VE2)
Pry-off tamper kit	ST400 (optional)

Detection

Max. detection range	16 m
Detection range	16 m
Undercrawl protection	Yes
Alarm memory	Yes
Alarm time	3 s

Wired/wireless

Wired-wireless	Wired

Inputs/outputs

Relay configuration	Isolated or 4k7 EOL
Remote control lines	Day/Night, Walk test

Physical

Colour	White
Mounting height	1.8 to 3 m

Environmental

Environment	Indoor

Regulatory

EN50131 grade	Grade 2



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57