ATS1190X4

ATS Smart Card Reader 4 pcs



Details

- Full epoxy filled weather proof construction
- Standard white snap-on cover (optional red, black, beige, grey)

ATS1190X4

ATS Smart Card Reader 4 pcs

Technische specificaties

System

Max. reader distance to panel	1500
Supported card types	HiTag2
Addressing type	Kartenadressierung, Tastatur Adressierung, Softwareadressierung
No. of LEDs	Tricolor
No. of covers included	4, White
Reader accessory	Optional fargige Abdeckungen

Technology

Reader type	Nahdistanz, Smartcard
Reader operating-transmitting frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Interface & connections

Interface	ATS RS-485, Wiegand
Connector type	Zopf
Pigtail length	250

Inputs/outputs

Inputs	Aufforderung zum Beenden
Outputs	1 Open Collector (25 mA)

Tamper type

Pry-off tamper	Yes

Operation

PIN keypad	No

Electrical

Power supply value	9 to 14 VDC
Current consumption	80 25

Physical

Physical dimensions	36 × 110 × 20 mm
Colour	Weiß
Material	Plastik
Mounting Type	Oberflächenmontage

Environmental

Vandal proof	No
Operating temperature	-35 to +66 °C
Environment	Drinnen
IP rating	IP54

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57