KE-DM3010R-IP

Botoneira endereçável inteligente da Série Excellence, à prova de intempéries

General

The KE-DM3000 Series is an intelligent range of addressable, Excellence Series manual call points. The KE-DM3010R-IP is a weatherproof, red, single action MCP with a House-on-Fire functional indication. It is delivered complete with resettable element, test connector and test key. Multiple optional accessories are available to facilitate most in- and outdoor installation requirements.

Aesthetics

This weatherproof single action MCP is a standard profile MCP suitable for surface mount installations. It is supplied with a colour matched weatherproof back box. With its designer dual, tricolour LEDs it offers 180°, clear local indication of its operational status, even from a side view. The clean face of the MCP is further enhanced by a front access & test key facility.

Installation & maintenance friendly

The front facing access for an aesthetically matching test key allows unhindered access regardless of the installation location. The MCP key doubles as a test and disassembly tool allowing removal of the MCP front cover without the need for additional tools.

Compatibility

The KE-DM3000 range may be used on all Kidde Excellence Series fire systems, and are also compatible with legacy Aritech fire systems. They can in many cases be deployed into existing systems without CIE configuration changes.



Detalhes

- Reliable single action manual call point for surface mounting
- Dual, tri-colour status indicators offers 180° alarm visibility
- Tamper resistant design with resettable or frangible element
- Unobtrusive front facing test facility
- Standard mounting options facilitates easy retrofitting to existing installations
- Back box with rear, top and bottom cable entry
- Screen connection terminal in the back box for electrically noisy installations
- Pluggable connector with link through facility for ease of installation and pre-commissioning testing
- An alarm flag on the face of the manual call point allows alarm indication even without alarm LEDs
- Fast, no-tools-required maintenance using the test key
- Up to 128 devices supported per loop

KE-DM3010R-IP

Botoneira endereçável inteligente da Série Excellence, à prova de intempéries

Especificações técnicas

General

Status indication	Dual LEDs, Alarm (red constant), Isolated (yellow constant), Fault (yellow blinking), Communication (green blinking)
User interface	LEDs, Alarm Flag
Compatibility	Excellence and legacy Aritech series fire systems
Connectivity	2-wire loop
Addressing method	Dip-Schalter

Electrical

Power supply type	Loop-Stromversorgung
Operating voltage	17 to 38 VDC
Current consumption	180 µA (Quiescent) 2.8 mA (Alarm)
Cable specification	0.404 to 2.05 mm
No. of cable cores	2
Terminals	4 (A+/A-;B+/B-)

Detection

Detection principle	Push button/switch
Monitoring	Activated, Fault, Off
Response time	< 3 s
Installation height	Determined by local regulation

Physical

Physical dimensions	108 x 108 x 69 mm
Net weight	267 g (w/ back box)
Colour	Rot (RAL 3028)
Mounting type	Wandmontage
Cable entries	3 x threaded MK20
Material (body)	Schwer entflammbares ABS
Functional marking	House on Fire

Environmental

Vandal proof	No
Operating temperature	−25 to +72°C
Storage temperature	−25 to +72°C
Relative humidity	10 to 95% noncondensing
Environment	Drinnen, Draussen
IP rating	IP67

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR
Standards	EN54:11

Produtos compatíveis

Categoria	Referência	Descrição
Detection device	N-MC-FC	Tampa "Flip" Transparente para Botoneira Inteligente
Detection device	N-MC-FE	Vidro p/operação por quebra (pack 10) para Botoneira Inteligente



KIDDE COMMERCIAL

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57