# KE-DBA-ADPW-ZIT

## Intelligent addressable base accessory - Ziton adapter (White)

### General


The KE-DBA-ADPW-KIL is an Excellence series base adapter. It allows easy migration form a legacy Kilsen KL7A series installation by offering the possibility to keep the legacy standard base installation intact, but convert to the new Excellence series intelligent detectors.

### Standard Base

The adapter base is designed to enable the new Excellence series detectors to be plugged in without any need for force - particularly useful when fitting to suspended ceilings. To make it even easier, the base has a "one way only"  fit.

The adapter base contains no electronic parts that could be damaged during installation. It automatically locks into the legacy standard base just like fitting a detector The adapter also supports the option to lock the Excellence series detector in place to avoid unauthorised detector removal.

As with all Excellence series standard bases, the Excellence series base adapter supports Excellence series address tags for neat product identification labeling.



### Details

- Allows the reuse of legacy Ziton ZP7 standard bases without installation modification in systems upgrading to the new intelligent Excellence series detectors
- Automatic locking to legacy base avoids adapter removal when the new detector is removed
- Supports the Excellence detector base locking option to prevent unauthorised removal of the Excellence series detector
- Standard Excellence series base already integrated
- Hides the legacy base for perfect colour matching to the new Excellence series detector
- Supports Excellence series address tags for neat labelling and device identification
- EN54 approved with the Excellence series detectors

# KE-DBA-ADPW-ZIT

## Intelligent addressable base accessory - Ziton adapter (White)

## Technical specifications

### General

| | |
|---|---|
| Compatibility | Ziton ZP7-SB1 standard detector bases |
| Connectivity | No wiring changes required |

### Physical

| | |
|---|---|
| Physical dimensions | 120.5 x 32.5 mm (Ø x h) |
| Net weight | 80 g |
| Colour | Traffic white (RAL9016) |
| Mounting type | Base mount |
| Material (body) | PC / ABS |

### Environmental


| | |
|---|---|
| Vandal proof | No |
| Operating temperature | −10 to +65°C |
| Storage temperature | −30 to +75°C |
| Relative humidity | 10 to 93% (noncondensing) |
| Environment | Indoor |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, UKCA, WEEE |
| Certification | CE |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Detection device | KE-DBA-TAGW | Intelligent addressable base accessory - address tag (white), supplied in packs of 10 |
| Detection device | KE-DP3020W | Excellence series intelligent addressable dual optical smoke detector |
| Detection device | KE-DP3021W | Excellence series intelligent addressable dual optical/heat detector |
| Detection device | KE-DT3001W-HAB | Excellence series intelligent addressable heat detector |




KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 2 June 2026 - 16:04