ATS8520-2

User management tool, USB version

Product overview

ATS8520 provides an easy, open look Windows® interface that simplifies the user management or control of Advisor Advanced or Advisor MASTER panels. Up to 20 panels can be managed separately. Each panel is configured one by one.

Upload / download

A PC running ATS8520 can be connected to a control panel either remotely via the built-in PSTN dialer or ethernet/GPRS connection. Changes made to user configuration can be up/downloaded (all data) or synchronized (changes only).

Remote Command and Control

All Advisor Advanced control panels can run a Command & Control session with the ATS8520. It will provide a complete overview of the panel status including zone, area, communication path, etc.
The ATS8520 can provide full control over the panel remotely based on the user options assigned.

Real time event log

A real-time event log shows all events as they happen with a time and date stamped description of the event. History can be viewed as a constantly visible window in the Command & Control view.

Supported languages

The ATS8520 supports following languages:
Danish, Norwegian, Finnish, Swedish, French, Turkish, Polish, Slowak, Czech, Dutch, English Irish, English UK, French, German, Italian, Portugal and Spanish.

User management

User management includes operations related to create, modify or remove users, PIN codes of users, card assignment, access right assignment or schedules and holidays.



Details

- User management tool for smaller systems, managing up to 20 panels separately
- Configure and modify users, assign cards and PIN codes
- Compatible with Axon and Advisor Advanced panels
- Microsoft SQL database
- Command & Control with live history
- Real time event logging
- Manage schedules and holidays

ATS8520-2

User management tool, USB version

Technical specifications

General

Product line	Advisor Advanced, ATS Master, Axon
Segmentation	Gewerblich
Software type	Management software
Supported technology	Zutrittskontrolle, Einbruch
Supported hardware	Advisor Advanced, ATS Master, Axon
Max. number of PC with ATS8520 connected	1
Max. number of panels connected at the same time	20
Number of panels in database	20

Software details

Software architecture	Autonome
License type	Freie Lizenz

System requirements

Supported operating system	Windows 10, Windows 7, Windows 8.x
Database support	SQL
Minimum system requirements	Intel Dual Core i5 with 4GB RAM Memory: 256 MB (minimum); 1GB (recommended) HDD: Up to 500 MB of available space may be required Display: 1024 x 768, 32-bit (minimum), Note: for Windows 7, Home and Starter Editions are not supported.

Physical

Net weight	80 g
Shipping weight	110 g

SQL Support

	ATS8500 is fully compatible with MS SQL versions: 2012, 2014, 2016.

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 September 2024 - 13:28