# TVM-2414

**TruVision 24" LED, VGA, HDMI, audio speaker, stereo audio In, Full HD, 1920 x 1080**

## Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI or VGA connections, these monitors are a great fit for today's demanding video surveillance market.
Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.

## Capabilities

The TVM-2414 is a 24" class monitor, offering HDMI and VGA connections. The monitor is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.



## Dettagli

- 24" LED Backlight
- Full HD resolution
- Ultra-thin body with ultra-thin border for 3 sides
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 4000:1 contrast ratio for crisp images
- Multiple inputs including VGA, HDMI

# TVM-2414

## TruVision 24" LED, VGA, HDMI, audio speaker, stereo audio In, Full HD, 1920 x 1080

## Specifiche tecniche

### General

| | |
|---|---|
| Technology | DEL |
| VESA compatibility | 100 x 100 mm |
| Included accessories | Manuel, Cordon d’alimentation |
| Bezel width | 1.8 mm (top/left/right), 21.4 mm (bottom) |

### Display

| | |
|---|---|
| Screen size | 23.8” |
| Aspect ratio | 16:9 |
| Contrast ratio | 4000:1 |
| Pixel pitch | 0.2745 (H) × 0.2745 (V) mm |
| Viewing angle (H/V) | 178° / 178° |
| Response time | 6.5 ms (typ) (G to G) OD 5 ms |
| Brightness | 250 cd / m² (typ.) |
| Recommended resolution | 1920 x 1080 @ 60Hz |
| Backlight | E-LED |
| Color depth | 8 bit |
| Active display area | 527.04 (H) × 296.46 mm (V) |
| Haze | Anti-Glare, 3H (Without Haze) |

### Interface

| | |
|---|---|
| BNC video I/O | Non |
| VGA video in | Yes |
| HDMI video in | 1 |
| PC stereo in | Yes |
| Audio out | No |

### Operations

| | |
|---|---|
| Controls | Power, Up/Down, Left/Right, Source, OSD Menu |
| OSD | English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish, Polish |
| Remote control support | No |

### Electrical

| | |
|---|---|
| Power supply type | 100 til 240 VAC |
| Power consumption | <25 W |
| Standby power consumption | ≤ 0.5 W |
| Power supply | DC 12 V, 2.5 A |

### Physical

| | |
|---|---|
| Physical dimensions | 538 × 326 × 37 (without stand)<br>538 × 407 × 186 (with stand) |
| Net weight | 2.63 kg |
| Shipping weight | 3.34 kg |
| Colour | Sort |
| Housing Type | Plastic |

### Environmental

| | |
|---|---|
| Operating temperature | 0 to 40°C |
| Storage temperature | -20 to 60°C |
| Relative humidity | 20 to 90% noncondensing |
| Environment | Indendør |

### Regulatory

| | |
|---|---|
| Compliancy | CE, UKCA |

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 20:20