AS700G3

Outdoor siren, plastic housing, NFA2P Grade 3

Product overview

The outdoor siren is a signaling device to alert others if an emergency arises. It is a very important addition to a security system as it ensures everyone on site knows about the alarm system activation.
This siren has coated electronics and IP44 rated for a variety of applications, especially in harsh environments.
Designed to comply against EN Grade 3 certification, the siren includes an enhanced protection against sabotage.
The battery and power supply are fully supervised.

As soon as an intrusion is detected, the outdoor siren triggers a powerful 105 dB sound signal.
Its sound and duration can be programmed and its battery has up to 60 hours autonomy.



Details

- Battery circuit protection with resettable fuse
- Enhanced tamper protection
- Aritech elegant design
- Self test every 24 hours to check the integrity of the battery and its charging circuit
- Engineer mode (for commissioning and to inhibit sounder operation)

AS700G3

Outdoor siren, plastic housing, NFA2P Grade 3

Technical specifications

General

Accessory group	Sirene
Type	Udendørs sirene
Sounder output	>101 dBA at 1m

Flash specifications

Current consumption	10 mA @ 13.8 V (quiescent)

Electrical

Power supply type	9 VAC
Operating voltage	9 to 15 V
Current consumption	100 mA at 9 to 15 VDC (typical)

Physical

Physical dimensions	203 x 260 x 81 mm
Net weight	1130 g
Colour	Hvid
Material	ABS

Environmental

Vandal proof	Yes
Operating temperature	-10 to 55°C
Storage temperature	-10 to 55°C
Relative humidity	<95% noncondensing
Environment	EN50130-5 ; Klasa II - Wewnątrz (ogólnie)
IP rating	IP44

Regulatory

Compliancy	CE
Certification	EN50131 Grade 3
Standards	NFA2P Grade 3

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 June 2026 - 15:08