DT2063N

2000 Series addressable heat detector with dual alarm LEDs and a remote indicator output



DT2063N

2000 Series addressable heat detector with dual alarm LEDs and a remote indicator output

Technische specificaties

General

Addressing method	Rotary switch

Electrical

Power supply type	Zasilanie pętlą

Detection

Monitoring	Alarm threshold
Alarm temperature (typical)	> +40°C

Physical

Colour	Śnieżnobiały (RAL 9001)
Mounting type	Loftmontering
Material (body)	Plastic

Environmental

Vandal proof	No
Application temperature (typical)	+25°C
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Compatibele producten

Categorie	Referentie	Beschrijving
Detection device	DB2002	Montagevoet 10 cm - 4 connectoren
Detection device	DB2004	2000 Series Detector Deep Base, 5 Terminals
Detection device	DB2016	Isolator Montagevoet 10 cm - 2 connectoren
Notification device	AI672	Optische alarm indicator
Notification device	AI673	Optische en akoestische nevenindicator
Notification device	DB2368IAS-W	2000 Series Base Sounder with Isolator - WHITE

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57