# N-IO-MBX-2

## DIN Rail Module Box

### General

The N-IO-MBX-2 is a surface mount enclosure designed for housing modules requiring a DIN rail mount. It's main function is to facilitate the easy installation and protection of these devices, whist keeping cabling accessible, secure and neat in the provided cable trunking inside the enclosure.



### Details

- Easy installations of DIN rail mount modules on pre-fitted DIN rails
- Pre-installed cable trunking for neat cabling
- House multiple DIN units in one location in an aesthetic enclosure

# N-IO-MBX-2
## DIN Rail Module Box

## Technical specifications

### Physical

| | |
|---|---|
| Physical dimensions | 612 x 417 x 110 mm (W x H x D) |
| Net weight | 7.3 kg |
| Colour | Branco puro (RAL 9010) |
| Material | Metal |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Environment | Indendør |
| IP rating | IP30 |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, WEEE |
| Certification | CE |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Interface unit | KE-IO3101 | Excellence series intelligent addressable 1 output unit with isolator |
| Interface unit | KE-IO3101-M | Excellence series intelligent addressable mains switching output unit with isolator |
| Interface unit | KE-IO3122 | Excellence series intelligent addressable 2 input / 2 output unit with isolator |
| Interface unit | KE-IO3144 | Excellence series intelligent addressable 4 input / 4 output unit with isolator |
| Interface unit | KE-IU3110 | Excellence series intelligent addressable 1 input unit with isolator |
| Interface unit | KE-IU3111-ZME | Excellence series intelligent addressable zone monitoring unit with isolator (ext. power) |

KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 24 September 2025 - 11:08