BS127N-A

Sealed lead-acid battery, 12 V, 7.2 Ah, for Intrusion/ Video/Access control applications

Overview

Used for emergency exit lights, warning signs, illumination, or security systems, it allows uninterrupted operations for a certain amount of time in case of power is down.

Application

This battery can be used for cyclic and standby applications as it has been designed to be more efficient, safer and more environmental friendly.



Details

- Maintenance free
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity
- Can be used for cyclic and standby applications
- High energy density

BS127N-A

Sealed lead-acid battery, 12 V, 7.2 Ah, for Intrusion/ Video/Access control applications

Technical specifications

General

Product type	Forseglet blybatteri

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	7.2 Ah

Charge / discharge

Max. charge voltage	13.8 VDC @ +20°C
Max. charge current	2.16 A
Max. discharge current	35 A

Temperature

Charging temperature	0 to 40°C
Discharging temperature	-15 to 50°C

Physical

Physical dimensions	151 x 94 x 65 mm
Net weight	2.678 kg
Shipping weight	2.678 kg
Colour	Sort
Material	ABS
Terminal type	Fast-on 4.8 mm

Environmental

Fire retardant	No
Vandal proof	No
Operating temperature	0 to 40°C
Storage temperature	-15 to 50°C
Environment	Indendør

Regulatory

Compliancy	RoHS 2, WEEE
Certification	VdS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:26